

DS30 Hazardous Location Plugs & Receptacles – 30 A

Devices rated for hazardous locations are not returnable.

SE Ratings

- Voltage**
600 VAC
- Current Interruption Capability**
Not for current interrupting
- Horsepower Ratings**

120V	1Ø	1 1/2 hp
240V	1Ø	3 hp
208V	3Ø	5 hp
240V	3Ø	5 hp
480V	3Ø	15 hp
600V	3Ø	15 hp
- Short Circuit Rating**
100kA Withstand
Tested with RK1 current limiting fuses sized at 400% of the highest full load motor ampacity.
- Environmental Ratings**
Type 4X
- Temperature Range**
Min -40°F/Max 104°F
See pg 258 for temps below -15°F.
- Wiring Capacity**
Min 14 AWG Max 4 AWG
Aux Contacts - Max 14 AWG
Based on THHN wire sizes
- Applicable Standards**
CSA C22.2 No. 182.1-07
C22.2 No. 213-M1987
- Hazardous Ratings**
Class I, Division 2, Groups ABCD, T6
Class I, Zone 2, IIC

Receptacle (female)



Inlet (male)



Hazardous Location DS30 lid is normally closed

! Don't forget to add installation accessories to your order

Voltage	Polarity	Part # Poly	Part # Poly
120V	1P+N+G	35-34165-xxx-HAZ	35-38165-xxx-HAZ
120 208V	3P+N+G	35-34167-xxx-HAZ	35-38167-xxx-HAZ
125V	1P+N+G	35-34075-xxx-HAZ	35-38075-xxx-HAZ
125 250V	2P+N+G	35-34076-xxx-HAZ	35-38076-xxx-HAZ
208V	2P+G	35-34162-xxx-HAZ	35-38162-xxx-HAZ
208V	3P+G	35-34163-xxx-HAZ	35-38163-xxx-HAZ
250V	2P+G	35-34072-xxx-HAZ	35-38072-xxx-HAZ
250V	3P+G	35-34073-xxx-HAZ	35-38073-xxx-HAZ
277V	1P+N+G	35-34045-xxx-HAZ	35-38045-xxx-HAZ
277 480V	3P+N+G	35-34047-xxx-HAZ	35-38047-xxx-HAZ
347 600V	3P+N+G	35-34147-xxx-HAZ	35-38147-xxx-HAZ
480V	2P+G	35-34042-xxx-HAZ	35-38042-xxx-HAZ
480V	3P+G	35-34043-xxx-HAZ	35-38043-xxx-HAZ
600V	2P+G	35-34142-xxx-HAZ	35-38142-xxx-HAZ
600V	3P+G	35-34143-xxx-HAZ	35-38143-xxx-HAZ

The xxx represents any and all device options; if no options are needed, the xxx suffix should be omitted.

Part Number Example

480V DS30 + 2 aux contacts
DS30 recept 3P+G = 35-34043-972-HAZ

480V DS30 with no options
DS30 recept 3P+G = 35-34043-HAZ

Receptacle Options	Suffix #	Inlet Options	Suffix #
With 2 Auxiliary/Pilot Contacts	Recept # - 972	With 2 Auxiliary/Pilot Contacts	Inlet # - 972
With 3 Auxiliary/Pilot Contacts	Recept # - 973	With 3 Auxiliary/Pilot Contacts	Inlet # - 973
With 4 Auxiliary/Pilot Contacts	Recept # - 974	With 4 Auxiliary/Pilot Contacts	Inlet # - 974
Open Lid Configuration	Recept # - NO	With No Lockout Hole	Inlet # - A155

Feature Spotlight – Screw-Type Locking Pawl



Zone 2/Division 2 DS30 receptacles feature a standard screw-type locking pawl. This required feature allows the user to lock the plug to the receptacle by tightening a screw on the pawl.



For added security, a lockout hole is included on the receptacle that enables the user to insert a 5/16" lock or locking pin to prevent the plug from being disconnected or to lock the receptacle lid closed.

! See pages 235-244 for detailed information on these options


INSTALLATION ACCESSORIES – SIZE 3

Accessories rated for hazardous locations are not returnable.

HANDLES

HANDLE w/NPT		Part # Poly	Part # Metal
	1/2"	553P0N05	5K3P0N05
	3/4"	553P0N07	5K3P0N07
	1"	553P0N10	5K3P0N10
	1 1/4"	553P0N12	5K3P0N12

For available cord grips, see pg 168.





POLY HANDLE w/Cable Range		
	.39 - 1.18"	553P0D30




Cable Range	NPT	Cable Range	NPT
.312 - .625"	1/2"	.660 - 1.000"	1"
.438 - .812"	3/4"	.875 - 1.375"	1 1/4"


NPT sizes are determined by the cable diameter and third party cord grip.


ANGLES


POLY ANGLE		
	30°	553M3
METAL ANGLE		
	0°	5K3M0
	30°	5K3M3
	70°	5K3M7

BOXES

POLY ANGLE WITH METAL BOX w/NPT				
	30°	1/2"	753C3N05	
	30°	3/4"	753C3N07	
	30°	1"	753C3N10	
	* 29.6 in ³	30°	1 1/4"	753C3N12
	* Interior volume with receptacle installed.			


METAL ANGLE WITH METAL BOX w/NPT				
	30°	1/2"	7K3C3N05	
	30°	3/4"	7K3C3N07	
	30°	1"	7K3C3N10	
	* 29.6 in ³	30°	1 1/4"	7K3C3N12
	* Interior volume with receptacle installed.			

POLY ANGLE WITH LARGER METAL BOX w/NPT				
	70°	1/2"	753C7N05	
	70°	3/4"	753C7N07	
	70°	1"	753C7N10	
	* 170.0 in ³	70°	1 1/4"	753C7N12
	* Interior volume with receptacle installed.			
70°	1 1/2"	753C7N15		


METAL ANGLE WITH METAL BOX w/NPT				
	70°	1/2"	7K3C7N05	
	70°	3/4"	7K3C7N07	
	70°	1"	7K3C7N10	
	* 27.7 in ³	70°	1 1/4"	7K3C7N12
	* Interior volume with receptacle installed.			

NPT on top or bottom (if rotated). For other NPT configurations, contact customer service.

MISCELLANEOUS ACCESSORIES

FINGER DRAWPLATES		
	61-6A346	Set of Two (2) Recommended for easier connector closure.

PROTECTIVE INLET/PLUG CAP		
	31-3A426	For Inlets/Plugs Only.

RECEPTACLE LOCKING PIN		
	LP-843	

Notes: For Zone 2 DS dimensions refer to DS dimensions on pgs 55-56.